



**PRODUCT NAME:**  
**Asphalt Revitalizer 55**

**DESCRIPTION**

**Asphalt Revitalizer 55** is a waterborne emulsion for revitalizing asphalt.

**BASIC USES**

For revitalizing or rejuvenating asphalt

- Parking lots
- Driveways
- Asphalted surfaces in parks

**MAJOR ADVANTAGES**

- Safe alternative to hot-applied bitumen or solvent-based products
- Non-water soluble, non-leaching
- Excellent stabilization
- Non-skid surface
- Ease of application
- Long Wearing
- Flexible & seamless, resistant to cracking & aging
- Freeze/Thaw Resistant
- Environmentally benign
- Salt resistant
- VOC free

**TECHNICAL AND PRODUCT DATA**

Percent Non-Volatile ..... 52.2  
pH ..... 6-9  
Specific Gravity ..... 1.02  
Odour ..... Slight Sweet  
Viscosity ..... 15 – 18sec Zahn #2  
Volatile Organic Compounds ..... 0 g/L  
Colour ..... Black

**SPECIFICATIONS**

- **OPSS 2510** – Ontario Provincial Standard Material Specification
- **OPSS 305** – Ontario Provincial Standard Material Specification for Granular Sealing

**PRECAUTIONS**

*See Safety Data Sheet*

**APPLICATION INSTRUCTIONS**

- Before applying, read associated Safety Data Sheet and follow guidance on proper personal protective equipment and material handling
- Do not store or use this material below 5°C
- Do not store where exposed to direct sunlight
- Revitalizer 55 is brushed, rolled or sprayed on
- Coverage is 300 ft<sup>2</sup> per gallon per coating
- Allow to dry between coats
- 2 coats are recommended
- Clean up with mineral spirits

**WARRANTY DISCLAIMER**

The information contained herein is based on available data and is provided for information only. CRC™ makes no warranties, guarantees or conditions, expressed or implied, regards the accuracy of the data or its use therein CRC™ will not be liable for any damages arising from the use of the information product described on this data sheet. Product data subject to change without notice. Unless otherwise stated, CRC™ sole warrantee shall be the replacement or refund of purchase price for any product found not to meet the above specifications.

CRC Coating Technologies Inc.™ 6254 Skyway Rd, PO Box 915 Smithville, ON L0R 2A0	TEL: 289-448-0157 TF: 888-292-5565 FAX: 905-527-0606	Email: info@crccoatings.com Web: www.crccoatings.com	CRC Coating Technologies Inc.™ 3909 Witmer Rd Ste 1014 Niagara Falls, NY 14305
--	--	---	--